

List of all GRP lubricant product ranges

Product Name	Classification	Main Applications	Main Features	Size	P/N
GRP 807 α	Oil additive For Engine Oil	Engine Oil, manual transmissions and automatic transmissions	Reduction of fuel consumption Improvement of operating efficiency	200cc	G01
GRP	GRP oil additive	Construction machinery, Machine factories, Metal processing, etc.	It is a [super-lubricant] with excellent overall lubrication characteristics that are incomparable to conventional general lubricants in terms of composition, effect, and stability.	1L 4 L 20 L	G2 G3 G4
GRP-TO	GRP oil additive	For equipment that uses turbine oil, such as compressors	The composition ratio is adjusted to the optimum ratio for turbine oil.	4 L 20 L	G50 G55
GRP-G	GRP oil additive	For equipment that uses gear oil, such as gear sets and reducers.	It greatly reduces scratches and wear on the metal surfaces caused by high sliding pressure.	1L 4 L 20 L	G70 G5 G6
NMW	Water-soluble Metal Processing Additive	Metal processing, Engine cooling Hydraulic equipment	NMW is a lubricant (cutting agent) for metal processing that boasts the highest level of technology.	4 L 20 L	G25 G26

Product Name	Classification	Operating Temperature Range	NLGI No.	Main Features	Size	P/N
Super Thixo Grease	General high performance extreme pressure grease	-35°C ~ +160°C	#0	THIXOGREASE is an epoch-making grease that has been developed based on the field of "lubrication chemistry + science" of the new generation and has fundamentally solved all the problems of conventional products.	400 g 17kg	G37 G19
Super Thixo Grease (Limited edition)	General high performance extreme pressure grease	-35°C ~ +160°C	#2		400 g 17kg	G16 G17
Ultra Super Thixo Grease	General high performance extreme pressure grease	-35°C ~ +180°C	#2		400 g 17kg	G74 G75
HTG300	High Temperature Grease	120°C ~ 300°C	#2	HTG was developed based on the conventional Thixo Grease tech- -nology to further extend its high temperature lifespan	400 g 17kg	G21 G51
HTG600	High Temperature Grease	200°C ~ 600°C	#00	High temperature ash lubrication	400 g 10kg	G20 G48
UWG7 Underwater Grease	For parts of equipment that constantly slide in water	0°C~100°C (Underwater) 0°C~150°C (In the air)	#2	UWG7 is a grease developed to function in water	400 g 17kg	G34 G61
STG3 Viscous Grease	Viscous Grease	-20°C~+80°C	#2	It is used in cases where conventional greases disperse due to centrifugal force or rapid air speed.	400 g	G22
GRP Oil Spray	Oil Spray			This is a super-lubricant with 5% GRP oil additive	300ml	G28
GRP Grease Spray	Grease Spray			Including GRP Thixo Grease #0	300ml	G29